

Catalogue of quick link cotton baling wire machine

Specification & Data

Machine Name	quick link cotton baling wire machine	Nominal Force	4000 kN
Hourly Output	4540 kg (20 bales) to 9080 kg (40 bales)	Power	85 kW to 153 kW (depending on output)
Model No.	QL-15-60	Bale Weight:	270 kg $\pm$ 10 kg





Technical data	Diameter of wire:				2.5mm-4mm
	wire	diameter	Length (Maximum)	Length (minimum)	Raw materials of steel wire (hot dipped)
	3mm	3	6000 mm	1500 mm	Carbon (C): 0.52%~0.60% Silicon (Si): 0.17%~0.37% Manganese (Mn): 0.50%~0.80% Sulfur (S): ≤0.035% Phosphorus (P): ≤0.035% Chromium (Cr): ≤0.25% Nickel (Ni): ≤0.30% Copper (Cu): ≤0.25%
	4mm	4	6000 mm	6000 mm	Same as above



WENZHOU CHANGS INTERNATIONAL

ROOM 604, FUJIA BUILDING, YULINJIA, LUCHENG, WENZHOU, ZHEJIANG, CHINA (WhasApp: +86 18621323471; Wechat +86 15057987463 WhatsApp call:+852-62802153 Web: strap-seal-machine.com)

	power	Motor1#,2.2KW	Motor 2#,0.74 KW	Total,2.94 KW		
	electrical box	Mechanical controlling	Start	stop		
	HS code	8463300000				
	Production rate	4540 kg (20 bales) to 9080 kg (40 bales)/hour				
	Motor power	2.94 kw				
	Voltage plans	V		Phase	HZ	
	A plan	380		3	60	
	B plan	220		3	60	
Technical data	C plan	220		Single phase		
Accessories	Straightening Block Bending Mandrel Top Bending Mandrel Wire Gripper			Wire Gripper Upper Cutter Lower Cutter Large Tension Spring Small Tension Spring		
Net Weight	900 KG					
Gross Weight	950 KG					
Machine Size	7200x578x1200					
Packing Size	7200x578x1200 mm=cubic meter 5 M3					
Packing method	Plywood box with reinforced steel structure					
Lead time	3-4 weeks after advance payment 30% One-year guarantee period, except quick-wear parts and natural damage or caused by human errors.					